



Xenic TAD33xxGE series diesel engine is specifically designed for generator equipment, marine, engineering machinery, industrial pump and farm machinery. It's made of alloy-cast iron of which shows high rigidity, strong vibration absorption, low noise, compact structure, better reliability and higher power.

Engine Type	Direct Injection, V-Type, 4-Stroke, Water Cooling
Intake Type	Turbo Charger / Air- air Intercooler
Rated Power	239 kW
Max Power	263 kW
Bore * Stroke	114*144 (mm)
Number Of Cylinder	6
Cylinder Type	Repleceable Wet Cylinder
Total Displacement	8.82 (L)
Specific Fuel Consumption	≤195 (g/kW•h)
Specific Oil Consumption	≤0,3 (g/kW•h)
Speed Governing Mode	Electronic Governor
Idle Speed	750 (rpm)
Rated Speed	1500 (rpm) / 1800 (rpm)
Starting Mode	Electrical Starting
Crankshaft Rotating Direction	Anti - Clockwise
Noise	≤105 (db)
Smoke	≤2.0
Flwheel Housing	SAE NO.2#
Flwheel	INO.11 ½#
Net Weight	3350 ± 50 (kg)
Length* Width*Height	2020*1780*1850 (mm)
Fuel Grade According to the Provisions of GB 252	General Environment No. 0 or - No.10 Light Diesel Oil
Southern China	No.10 Light diesel oil
Nourthern China	No-35 or Lower Pour Point Light Diesel Oil
Engine Oil According to the Provisions of GB 11122	CF15W/40 (Below environment temperature - 5 ° C)
First Step Load	73%



Key Features

- Adopted iron casting structure to the body, improved the integral structure and performance. Proper design and better sealing ability.
- Utilized 4 valves per cylinderi reduces the resistance to improve the air intake ability, better fuel combustion with high-performance P-type fuel injector.
- Applied inner cooling channel structure, not only reduce the contact stress between the camshaft and push-rod, but also the wear ratio, ensure the engine reliability.
- Adopted maas oil flow bump assy in order to ensure the lubrication and cooling ability.

Dimensions

